


PIN	SYMBOL	PIN	SYMBOL
1	LEDK	28	R0
2	LEDK	29	R1
3	LEDA	30	R2
4	LEDA	31	R3
5	NC	32	R4
6	NC	33	R5
7	NC	34	R6
8	/RESET	35	R7
9	SPENA	36	HSYNC
10	SPCLK	37	VSYNC
11	SPDAT	38	DCLK
12	B0	39	NC
13	B1	40	NC
14	B2	41	VDD
15	B3	42	VDD
16	B4	43	NC
17	B5	44	NC
18	B6	45	NC
19	B7	46	NC
20	G0	47	NC
21	G1	48	SEL2
22	G2	49	SEL1
23	G3	50	SEL0
24	G4	51	NC
25	G5	52	DE
26	G6	53	GND
27	G7	54	GND

LT035A-02A

Notes:

- 3.5" Transmissive, Normally-White TFT LCD Module
- View Direction: 6:00
- LCD Drivers: HX8238-D
- Interface: 24-Bit RGB/8-BIT RGB/CCIR656/CCIR601
- Operation Temp.: -20°C to 70°C
- Storage Temp.: -30°C to 80°C
- VDD=3.0V to 3.6V



DWN.	YDY	TITLE	LCM OUTLINE DIMENSION		
CHK.	LYJ	PART NO.	LT035A-02A		
APPD.	LY	DWG. NO.	LT035A-02A-WXC		
REV.	C	UNIT	mm	PROJECTION	
DATE	2018.03.20	SCALE	NTS	SHEET	1 OF 1